



Premium Wet/Dry Roofing Cement

COMPLIANCE: Exceeds performance requirements of ASTM D 6511, ASTM D 3409, ASTM D 4586, TYPE I. ASBESTOS FREE.

DESCRIPTION: Stelco™ Premium Grade Roofing Cement is a high quality Flashing Cement made with select asphalt, fibers and solvents. It is formulated for use with built-up systems, modified bitumen membranes (APP & SBS), base sheets, ply sheets, shingles and other approved surfaces. Stelco Premium Grade Roofing Cement can be used on vertical walls, flashings, penetrations, skylights, around drains and many other areas. Its unique formulation will not sag in the summer heat and even sticks in the rain or under ponding water. This high quality product is available exclusively to professional installers.

NOTE: DO NOT use on TPO, EPDM, PVC or other rubber/plastic single ply membranes.

PREPARATION: All surfaces must have proper drainage and be clean, and free of surface rust and any other foreign matter. Excessive particulate surfacing materials on modified membranes must be removed (sweeping with a stiff broom is recommended) prior to application. On reroofing applications, all deck and existing membrane repairs should be made first. Severely weathered BUR membranes may require a pre-application of an asphalt primer. Metal surfaces must have all rust and scale removed. DO NOT HEAT OR THIN.

FOR BEST RESULTS: Apply on clear sunny day when surface temperatures are between 40° and 100° F. In colder weather product should be stored in heated room (65° to 80° F.) at least 24 hours prior to application. After a minimum of 45 days cure time, apply a reflective coating. This will greatly extend the life of the roof.

APPLICATION: For exterior use only. Protective clothing and eyewear should be used during application of this product. Three Course Method: Apply with trowel or putty knife, working material to an even consistency over and into the area to be repaired. Apply 1/8" to 1/4" thick, two to three inches beyond the problem area. Then press a strip of reinforcing fabric or mesh into the cements and cover with an additional layer of flashing cement. Five Course Method: Complete 3 course directions above. Then press a second strip of reinforcement into the uncured cements and cover with an additional layer of flashing cement. Upon completion of your 3 or 5 course repair, form a cant with the cement around chimneys and other roof projections. Coverage rate is approximately 12 1/2 sq. ft. per gallon when applied 1/8" thick. For best results during reroofing, cut the mod-bit sheets to a maximum of 18 ft. lengths and allow to relax on job site before application.

PRECAUTIONS: When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110° F. Do not reuse empty containers. Do not use in drinking water or food systems. Seal container when not in use.

CLEAN-UP: Clean tools with paint thinner or mineral spirits.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon	8.0-9.0 lbs.
Consistency	Trowel
Application Temperatures	35° - 120°F
Flash Point	105°F
Clean-up Tools	Paint Thinner, Mineral Spirits

Approx. Shipping Weights: (Note: All approx. weights include container.)

1 gallon (3.8L)	9 lbs.
(6) 1 gallon containers/case	54 lbs.
3 gallons (11.4L)	27 lbs.
5 gallons (18.9L)	45 lbs.

**CAUTION! – COMBUSTIBLE MIXTURE.
HARMFUL OR FATAL IF SWALLOWED.
KEEP OUT OF REACH OF CHILDREN.
EYE, SKIN AND RESPIRATORY IRRITANT.
USE WITH ADEQUATE VENTILATION
FOR EXTERIOR USE ONLY.**

Contains Petroleum Distillate. Keep away from heat, sparks and open flame. If swallowed DO NOT induce vomiting. Call physician immediately. In case of : Eye contact - flush with large amounts of room temperature water for 15 minutes; Skin contact - wash thoroughly with soap and water; Irregular or stopped breathing - administer oxygen, give artificial respiration and get medical attention immediately. Avoid prolonged breathing of vapor or spray mist.

VOC/VOS - Less than 250 g/L max. (2.1 lbs./gal.)

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

LIMITED WARRANTY AND DISCLAIMER: Stelco™ Manufacturing, Inc, a Pennsylvania Corporation, warrants to the original purchaser, that this product will be free from any manufacturing defects that will materially affect the products ability to perform as stated on the product label. If you notify us of a defect and provide proof of purchase, we will replace the defective product at no cost to you. This limited warranty is the sole and exclusive remedy for any such defective product. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESSED OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND / OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE, AND STELCO MANUFACTURING, INC., WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

©2010 Stelwagon Roofing Supply Inc.
Manufactured for / Fabricado por:
Stelwagon Roofing Supply Inc.
10096 Sandmeyer Lane
Philadelphia, PA 19116

See MSDS for more info



Stelwagon Roofing Supply Inc. • 10096 Sandmeyer Lane • Philadelphia, PA 19116
Phone: (866) 606-6326