



CONGO MALAYAN

COMPLIANCE: Fed Spec SS-C-153 Type 1 (Asbestos Free). Exceeds performance requirements of ASTM D3409 and ASTM D4586, TYPE I. ASBESTOS FREE.

DESCRIPTION: Congo Malayan is a high performance rubber modified flashing cement specially formulated for the professional roofer. Congo Malayan is formulated using a special blend of SBS rubber which creates an extremely versatile mastic. This special blend of SBS polymers provides superior adhesion to wet surfaces, allows for bonding under water and is ideal for temporary or permanent repairs. Congo Malayan is the the roofing contractors number one choice for sealing and repairing seams, cracks and holes in spudded gravel, mineral surfaced cap sheet, smooth surface asphalt roofs, most APP and SBS membranes and shingle roofs. It can also be used for areas around chimneys, vent pipes, gravel guards, down spouts and concrete surfaces. Congo Malayan is also an ideal utility mastic for use in below grade waterproofing and damp-proofing systems.

PREPARATION: All surfaces must be clean, have proper drainage and be free of surface rust, dust and any other foreign matter. DO NOT HEAT OR THIN.

FOR BEST RESULTS: Apply when surface temperatures are between 50 °F and 120 °F. In colder weather, product should be stored in heated room (65 °F to 80 °F) at least 24 hours prior to application. Product formulated to be used year round. Clean tools with paint thinner or mineral spirits.

APPLICATION: For exterior use only. Protective clothing, gloves and eye wear should be used during application of these products. Apply with a trowel or putty knife. Work material to an even consistency over and into the area to be repaired. Using the “3-course” method, apply cement 1/8” thick, two or three inches beyond the problem area. Then reinforce the repair and embed a strip of polyester, fiberglass or cotton reinforcing fabric. Brush fabric to ensure it is fully saturated from the bottom side up. Finally, cover the fabric with an additional layer of cement. Form a feathered edge with cement where chimneys, vent pipes, and other projections meet the roof line. For best results, protect completed repair with a reflective coating. Coverage rate is approximately 12 1/2 sq. ft. per gallon when applied 1/8” thick

HANDLING & STORAGE PRECAUTIONS: When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110 °F. Do not reuse empty containers. Do not use in drinking water or food systems.

CLEAN-UP: Clean tools with paint thinner or mineral spirits.

©2015 Stelwag Roofing Supply Inc.
Manufactured for / Fabricado por:
Stelwag Roofing Supply Inc.
10096 Sandmeyer Lane
Philadelphia, PA 19116

See SDS for more info

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Weight Per Gallon	8.5- 9.0 lbs.
Adhesion Underwater	Excellent
Application Tools	Trowel
Application Temperatures	35 °F - 120 °F
Clean-up Tools	Paint Thinner, Mineral Spirits

*NOTE: Percentages listed are + or - 5%

Approx. Shipping Weights: (Note: All approx. weights include container)

3 gallons (11.4L)	28 lbs.
5 gallons (18.9L)	46 lbs.

VOC: <240 g/L (less water and exempt)

WARRANTY AND DISCLAIMER: Stelco™ Manufacturing, Inc, a Pennsylvania Corporation, warrants to the original purchaser, that this product will be free from any manufacturing defects that will materially affect the products ability to perform as stated on the product label. If you notify us of a defect and provide proof of purchase, we will replace the defective product at no cost to you. This limited warranty is the sole and exclusive remedy for any such defective product.

THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESSED OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND / OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE, AND STELCO MANUFACTURING, INC., WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

