

<b>Material Safety Data Sheet</b> May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.		<b>U.S. Department of Labor</b> Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072	
IDENTITY (As Used on Label and List) BITUTAK COM - Smooth		APP Modified Bitumen Roofing Material	
<b>Section I – Product and Company Identification</b>			
Manufacturer's Name Performance Roof Systems, Inc.		Emergency Telephone Number 800-727-9872	
Address 4821 Chelsea Ave. Kansas City, MO 64130		Telephone Number for Information 800-727-9872	
		Internet: www.Derbigum.com	
Date Prepared: May 22, 2006		Date Revised: May 22, 2006	
<b>Section II - Hazardous Ingredients/Identity Information</b>			
Hazardous Components Identity: (Specific Chemical Common Name(s))		CAS NO.	ACGIH TLV
% (optional)			
Roofing Sheet composed of:			
Petroleum Asphalt	8052-42-4	5mg/m3*	50-70
Polypropylene	9003-07-0	Not established	18-30
Talc Stabilizer	14807-96-6	N/A	0-10
Limestone	1317-65-3	5 mg/m3	5-23
Non-Woven Polyester	Not Available	Not established	5-25
Sand Dusting	(parting agent)	14808-60-7	10 mg/m3
Dry Talc Dusting			3-25
* As Fumes			
<b>Section III - Physical / Chemical Characteristics</b>			
Boiling Point	> 900°F	Specific Gravity (H <sub>2</sub> O =1)	0.9 - 1.1
Vapor Pressure (mm Hg.)	< 0.1	Melting Point	N/A
Vapor Density (AIR=1)	> 20	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water: Nil			
Appearance and Odor: Black appearance, characteristic petroleum, slight asphalt odor.			
<b>Section IV - Fire and explosion Hazard Data</b>			
Flash Point (Method Used)	520-650° F (ASTM D92)	Flammable Limits	LEL 1% UEL 6%
		>750°F	
Extinguishing Media: CO <sub>2</sub> , Foam, dry chemical			
Special Fire Fighting Procedures: Use air supplied breathing equipment for enclosed area and treat as a fuel oil			
Unusual Fire and Explosion Hazards: NONE			
In the event of fire, use normal fire fighting procedures to prevent inhalation of smoke and gases.			
(Reproduce locally)			OSHA 174

<b>Section V - Reactivity Data</b>			
Stability	Unstable		Conditions to Avoid
	Stable	X	N/A under normal warehouse storage
Incompatibility (Materials to avoid): Avoid contact with concentrated acids, hydrocarbons, oils			
Hazardous Decomposition or Byproducts: Asphalt fumes may occur on overheating			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	Overheating may cause fire
<b>Section VI - Health Hazard Data</b>			
Route(s) of Entry:		Inhalation?	Skin? Ingestion?
Yes-During heat application of product generating asphalt fumes.			
Health Hazards (Acute and Chronic)			
Acute: Nose and throat irritation. May cause dizziness.			
Chronic: There are no studies indicating asphalt causes cancer or respiratory damage in man.			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
Signs and Symptoms of Exposure: Nose and throat, eye irritation			
Medical Conditions Generally Aggravated by Exposure: None Known			
Emergency and First Aid Procedures: Remove individual to fresh air. If irritation persists, seek medical attention.			
<b>Section VII - Precautions for Safe Handling and Use</b>			
Steps to Be Taken in Case Material is Released or Spilled			
No special precautions: use good housekeeping			
Waste Disposal Method: Dispose of in accordance with local, state and federal regulations. If you are unsure of the regulations, contact your local Public Health Department, or the local Environmental Protection Agency (EPA).			
Precautions to Be Taken in Handling and Storing: Warehouse storage should be in accordance with package directions, if any, material should be kept on pallets and protected from moisture.			
Other Precautions: none			
<b>Section VIII - Control Measures</b>			
Respiratory Protection (Specify Type): N/A under normal conditions of use.			
Ventilation	Local Exhaust		Special: None
	Mechanical (General): N/A		Other
Protective Gloves: Yes, leather or cotton gloves are recommended.		Eye Protection: Not normally necessary	
Other Protective Clothing or Equipment: Long sleeve shirt, trousers, smooth bottom work shoes.			
Work/Hygienic Practices: Wash hands after application.			