



# MATERIAL SAFETY DATA SHEET



## SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### MATERIAL NAME: ASPHALT ROLLED ROOFING

PRODUCT/TRADE NAME: CT-10124: Black Diamond® Base Sheet (BDBS); Flintlastic® UltraGlass SA  
CT-10060: Flintlastic® NailBase, Flintlastic® PlyBase, WinterGuard® HT,  
MetaLayment™

PRODUCT USE: WEATHERPROOFING

PRODUCT DESCRIPTION: SELF ADHERING MODIFIED ROLL ROOFING MEMBRANE

CHEMICAL NAME: Mixture  
CAS NUMBER: None Assigned  
EINECS: None Assigned  
MOLECULAR FORMULA: No Data Available

### Company Identification

CERTAINTEED CORPORATION  
P.O. Box 860  
Valley Forge, PA 19482  
United States

WEB ADDRESS: www.certainteed.com

### Phone Numbers

Technical Information: (610) 341-7000 - 9 AM – 5 PM (Eastern Time – USA)

Emergency: (800) 424-9300 - EMERGENCY TELEPHONE: CHEMTREC  
Emergency: (703) 527-3887 - OUTSIDE OF THE U.S. CHEMTREC

PREPARATION DATE: 1/1/2009  
LAST REVISION DATE: 8/1/1994

## SECTION 2 - HAZARDS IDENTIFICATION

### Emergency Overview

*Under United States Regulations (29 CFR 1900.1200 - Hazard Communication Standard) the products listed above are exempt as articles under stated normal conditions of use. In Canada, these products are considered manufactured articles under the Workplace Hazardous Materials Information System (WHMIS) and are exempt. Under normal conditions of use the products listed in this MSDS are not expected to pose a physical hazard or health risk to humans. These products do not contain any form of asbestos materials.*

*The component exposure limits and other information in this document are provided for circumstances such as*

heating (above 250°F), burning, cutting, sanding and/or grinding when there is a potential for exposure to these components.

If heated, this product may cause temporary irritation to the upper respiratory system. Avoid inhalation as temporary irritation may occur. Mechanical irritation may occur. Wear appropriate personal protective equipment as described in Section 8.

## GHS

Temporary respiratory irritation may occur. Avoid breathing vapors/fumes. Contaminated work clothing should not be allowed out of the workplace. Wash thoroughly after handling. Wear protective gloves and NIOSH approved respirator if exposed to dust or if material is heated.



### NFPA/HMIS® RATINGS:

	<u>Health</u>	<u>Fire</u>	<u>Reactivity</u>	<u>Degree of Hazard</u>
				0 - Minimal (Insignificant)
				1 - Slight
				2 - Moderate
				3 - Serious (High)
				4 - Severe (Extreme)
				* - Chronic Health Effect(s)
NFPA RATING:	1	1	0	
HMIS®* RATING:	1*	1	0	

\*HMIS® is a registered trademark of the National Paint and Coatings Association

PHYSICAL FORM: Solid

COLOR: Black

ODOR: Mild petroleum odor

HAZARDS: Mild/Slight Irritant; Mechanical Irritant

ROUTE OF ENTRY: Inhalation

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing lung conditions which may be aggravated if fumes/dusts are inhaled.

POTENTIAL HEALTH EFFECTS: Under normal conditions of use these products are not expected to cause a physical hazard or health risk to humans.

### INHALATION:

ACUTE (IMMEDIATE): Temporary irritation of nose and throat may occur.

CHRONIC (DELAYED): This product contains crystalline silica which is listed by IARC as a suspect carcinogen.

Silicosis (pulmonary fibrosis or severe lung scarring) may occur if exposed to high levels or repeated encounters with dust. Exposure to airborne particles that exceed the limits listed may cause lung cancer.

This product also contains petroleum asphalt. If heated, there is limited evidence that derivatives of asphalt fumes may cause carcinogenic effects in animals. There is inadequate evidence to support that asphalt fumes alone are carcinogenic to humans. This product contains fiber glass fibers which are bound in the final product. Under normal conditions of use there is little chance of release in most emergency situations.

**SKIN:**

ACUTE (IMMEDIATE): Mechanical irritation of the skin/skin abrasion may occur characterized by itching or redness. Drying of skin and dermatitis may occur following prolonged exposures.

CHRONIC (DELAYED): No data available

**EYE:**

ACUTE (IMMEDIATE): Mechanical irritation of the eye may occur characterized by itching or redness.

CHRONIC (DELAYED): No data available

**INGESTION:**

ACUTE (IMMEDIATE): Ingestion of this product is unlikely.

CHRONIC (DELAYED): No data available

**MUTAGENIC EFFECTS:** None

**CARCINOGENIC EFFECTS:** When used under normal conditions, this product is not considered a carcinogen.

This product contains petroleum asphalt. Asphalt fumes arise from hot asphalt. Asphalt fumes (CAS # 8052-42-4): In 1985/87, IARC (International Agency for Research on Cancer) concluded the following: (a) Bitumens are not classifiable as to their carcinogenicity to humans (Group 3). (b) Extracts of steam- and air-refined bitumens are possibly carcinogenic to humans (Group 2B). IARC found that evidence for carcinogenicity from animal studies was: inadequate for undiluted air-refined bitumens; limited for steam-refined and cracking residue bitumens; sufficient for extracts of steam-refined and air-refined bitumen. IARC found that human evidence for carcinogenicity of asphalt fumes was inadequate. Studies of roofers indicated an excess of cancers; however, IARC concluded that, since roofers may be exposed also to coal-tar pitches and other materials, "the excess cancer risk cannot be attributed specifically to bitumens." In 1994, a published review of 20 epidemiology studies of asphalt workers and roofers agreed with IARC, that current human evidence is inadequate for the carcinogenicity of asphalt fumes in humans. Trace amounts of polynuclear aromatic hydrocarbons (PAHs) may be present in some asphalts and can be released upon excessive heating, which results in thermal cracking of the asphalt compounds. Some of these PAHs have been identified as having the potential to induce carcinogenic and reproductive health effects.

This product contains crystalline silica. IARC Monographs on Evaluation of Carcinogenic Risk of Chemicals to Humans (Monograph 68, 1997) concludes that there is sufficient evidence for the carcinogenicity of crystalline to humans, IARC (Group I). Crystalline Silica is classified as a Known Carcinogen according to the NTP.

This product contains glass wool insulation fibers. Following a thorough review of all the medical-scientific data available at a meeting in October 2001, the IARC panel lowered the classification for glass wool insulation fibers from a Group 2B classification ("possibly carcinogenic to humans") to a Group 3 classification ("not classifiable as to carcinogenicity to humans"). IARC said that there is "no evidence of increased risks of lung cancer or of mesothelioma from occupational exposures during manufacturing of these materials, and inadequate evidence over all of any cancer risk."

**REPRODUCTIVE EFFECTS:** None

**OTHER HEALTH EFFECTS:** None

See Section 12 for Ecological Information

## SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

### Composition/Information on Ingredients

Product(s) Containing Component	Chemical Name	CAS	%(weight)	UN;EINICS	LD50/LC50	EU	OSHA PEL/TWA	ACGIH TLV/TWA	NIOSH REL
---------------------------------	---------------	-----	-----------	-----------	-----------	----	--------------	---------------	-----------

Black Diamond Base Sheet (BDBS), Flintlastic® UltraGlass SA, Flintlastic® NailBase, Flintlastic® PlyBase, WinterGuard HT, MetaLayment™ contains:	Asphalt	8052-42-4	30% TO 70%	NA1999; 232-490-9	NDA	NDA	None	0.5 mg/m3	5 mg/m3
Black Diamond Base Sheet (BDBS), Flintlastic® UltraGlass SA, Flintlastic® NailBase, Flintlastic® PlyBase, WinterGuard HT, MetaLayment™ contains:	Calcium Carbonate	1317-65-3	5% TO 25%	215-279-6	NDA	NDA	15 mg/m3	None	10 mg/m3
Black Diamond Base Sheet (BDBS), Flintlastic® UltraGlass SA, Flintlastic® NailBase, Flintlastic® PlyBase, WinterGuard HT, MetaLayment™ contains:	Fibrous glass	65997-17-3	< 10	266-046-0	NDA	NDA	1f/cc (continuous filament glass fibers)	1f/cc (respirable fibers)	5 mg/m3 (total dust)
Black Diamond Base Sheet (BDBS), Flintlastic® UltraGlass SA, Flintlastic® NailBase, Flintlastic® PlyBase, WinterGuard HT, MetaLayment™ contains:	SBS Polymer	NDA	< 20	NDA	NDA	NDA	None	None	None
Black Diamond Base Sheet (BDBS) contains:	Slag	NDA	20% TO 40%	NDA	NDA	NDA	15 mg/m3	10 mg/m3	None
Black Diamond Base Sheet (BDBS), Flintlastic® UltraGlass SA, Flintlastic® NailBase, Flintlastic® PlyBase, WinterGuard HT, MetaLayment™ contains:	Polyolefin	NDA	< 10%	NDA	NDA	NDA	None	None	None
Flintlastic® UntraGlass SA, Flintlastic® NailBase, Flintlastic® PlyBase, WinterGuard HT, MetaLayment™ contains:	Silica, crystalline - quartz	14808-60-7	0% TO 20%	238-878-4	NDA	NDA	10 mg/m3 (% SiO2 + 2)	0.025 mg/m3	0.05 mg/m3

*Under United States Regulations (29 CFR 1900.1200 - Hazard Communication Standard) the products listed above are exempt as articles under stated normal conditions of use. In Canada, these products are considered manufactured articles under the Workplace Hazardous Materials Information System (WHMIS) and are exempt.*

See Section 11 for Toxicological Information

## SECTION 4 - FIRST AID MEASURES

INHALATION: Remove to fresh air, apply artificial respiration and/or oxygen if necessary and get medical attention.

SKIN: Remove contaminated clothing and wash exposed skin with soap and water. If irritation develops or persists, seek medical attention.

EYE: If foreign matter enters eyes, immediately flush with large amounts of water for at least 15 minutes or until irritation subsides.

INGESTION: Consult a physician if unusual reaction is noted. Product is not intended nor is it likely to be ingested or eaten.

See Section 2 for Potential Health Effects

## SECTION 5 - FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Use water, foam, CO2 or dry chemical extinguishers to contain fire.

UNSUITABLE EXTINGUISHING MEDIA: No data available

FIREFIGHTING PROCEDURES: Fire fighters should avoid inhaling any combustion products.

Firefighters should wear full-face, self contained breathing apparatus and impervious protective clothing to avoid smoke inhalation and lack of oxygen.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Burning of this product will produce thick black smoke.

HAZARDOUS COMBUSTION PRODUCTS: If burned, the materials could release toxic fumes and smoke. Incomplete thermal oxidation can produce hydrogen cyanide, carbon monoxide, carbon dioxide, ammonia, formaldehyde and other low molecular weight hydrocarbons and oxides of sulfur, nitrogen, calcium and magnesium.

FLASH POINT: NA

FLASH POINT TEST TYPE: N/A

EXPLOSION LIMITS

UPPER: N/A LOWER: N/A

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Not applicable

EMERGENCY PROCEDURES: Not applicable

CONTAINMENT/CLEAN-UP MEASURES: Pick up large pieces. Vacuum dust. If sweeping is necessary, use a dust suppressant such as water. These procedures will help to minimize potential exposures. Scoop up material and put into a suitable container for disposal as a non-hazardous waste.

## SECTION 7 - HANDLING AND STORAGE

HANDLING: Do not breathe dusts or fumes generated from cutting or heating this material. Keep this product away from heat, sparks, or open flame. Use this product with adequate ventilation. Always wash work clothes separately from other clothing. Wash thoroughly after handling. Use personal protective equipment as described in Section 8.

STORAGE: Store indoors in a cool, dry, well-ventilated area. Do not handle or store near an open flame, heat or other sources of ignition.

## SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

PPE:



**RESPIRATORY PROTECTION:** Respiratory protection is not normally required. Use a NIOSH approved/certified respirator when the exposure limits are exceeded. Use a particulate filter respirator for particulate concentrations exceeding the Occupational Exposure Limit.

**EYE/FACE PROTECTION:** Safety glasses with side shields should be worn at a minimum.

**SKIN/BODY PROTECTION:** Leather or cotton gloves may be worn to prevent skin contact and irritation. Normal work clothing (long sleeved shirts and long pants) is recommended.

**GENERAL INDUSTRIAL HYGIENE CONSIDERATIONS:** Use good industrial hygiene practices in handling this material. Availability of eye wash fountains are recommended.

**ENGINEERING MEASURES/CONTROLS:** No special ventilation systems are required under normal conditions of use.

LISTED EXPOSURE LIMITS:

**US State California**

- Asphalt (8052-42-4): **PELs:** (5 mg/m<sup>3</sup> PEL)
- Silica, crystalline - quartz (14808-60-7): **PELs:** (1.0 fiber/cc PEL; 0.5 mg/m<sup>3</sup> PEL (respirable dust))

**United States - ACGIH**

- Asphalt (8052-42-4): **TWAs:** (0.5 mg/m<sup>3</sup> TWA (inhalable fraction, as benzene-soluble aerosol)) | **Carcinogens:** (A4 - Not Classifiable as a Human Carcinogen (as benzene soluble aerosol)) | **TLV Basis - Critical Effects:** (irritation (as benzene-soluble aerosol))
- Silica, crystalline - quartz (14808-60-7): **TLVs:** (0.025 mg/m<sup>3</sup> TWA (respirable fraction); A2 - suspected human carcinogen; TLV
- Fibrous Glass (65997-17-3): **TWAs:** (1f/cc (Synthetic Vitreous Fibers – continuous filament glass fibers))

**United States – OSHA**

- Calcium carbonate (1317-65-3): **TWAs:** (15 mg/m<sup>3</sup> TWA (total dust); 5 mg/m<sup>3</sup> TWA (respirable fraction)) | **TWAs:** (15 mg/m<sup>3</sup> TWA (total dust); 5 mg/m<sup>3</sup> TWA (respirable fraction))
- Silica, crystalline - quartz (14808-60-7): **Mineral Dusts:** (((250)/(%SiO<sub>2</sub> + 5) mppcf TWA (respirable)); ((10 mg/m<sup>3</sup>)/(%SiO<sub>2</sub> + 2) mppcf TWA (respirable)); ((30 mg/m<sup>3</sup>)/(%SiO<sub>2</sub> + 2) mppcf TWA (Total Dust))) | **TWAs:** (0.1 mg/m<sup>3</sup> TWA (respirable dust))
- Fibrous Glass (65997-17-3): **TWA:** (15 mg/m<sup>3</sup> (total nuisance dust)); (5 mg/m<sup>3</sup> (respirable nuisance dust)) **NAIMA PEL:** 1f/cc (continuous filament glass fibers)

**United States - NIOSH**

- Asphalt (8052-42-4): **Ceiling Limits:** (5 mg/m<sup>3</sup> Ceiling (15 min, fumes))
- Calcium carbonate (1317-65-3): **TWAs:** (10 mg/m<sup>3</sup> TWA (total dust); 5 mg/m<sup>3</sup> TWA (respirable dust)) |
- Silica, crystalline - quartz (14808-60-7): **TWAs:** (0.05 mg/m<sup>3</sup> TWA (respirable dust)) |
- Fibrous Glass (65997-17-3): **REL/TWA:** (5 mg/m<sup>3</sup> (total glass dust)); (3f/cc (respirable fibers))

**Canada – British Columbia**

- Fibrous Glass (65997-17-3): 1 fiber/cm<sup>3</sup> TWA (fibers longer than 5 µm, with an aspect ratio of equal to/greater than 3:1) (related to Glass wool fibers)

**Canada – Manitoba**

- Fibrous Glass (65997-17-3): 1 fiber/cm<sup>3</sup> TWA (respirable fibers, length >5 µm, aspect ratio ≥3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination) (related to Glass wool fibers)

**Canada – New Brunswick**

- Fibrous Glass (65997-17-3): 1 fibre/cm<sup>3</sup> TWA (fibers longer than 5 µm with a diameter less than 3 µm, aspect ratio greater than 5:1) (related to Glass wool fibers)

**Canada – Northwest Territories**

- Fibrous Glass (65997-17-3): 3 fibres/cm<sup>3</sup> TWA (with a diameter ≤3.5 µm and a length ≥10 µm); 5 mg/m<sup>3</sup> TWA (total mass) (related to Mineral wool fiber)

**Canada – Nova Scotia**

- Fibrous Glass (65997-17-3): 1 fiber/cm<sup>3</sup> TWA (respirable fibers, length >5 µm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination) (related to Glass wool fibers)

**Canada – Nunavut**

- Fibrous Glass (65997-17-3): 3 fibre/cm<sup>3</sup> TWA (with a diameter <=3.5 µm and a length >=10 µm); 5 mg/m<sup>3</sup> TWA (total mass) (related to Mineral wool fiber)

**Canada – Ontario**

- Fibrous Glass (65997-17-3): 1 fibres/cm<sup>3</sup> TWAEV (respirable, length>5 microns, aspect ratio>= 3.1) (related to Glass wool fibers)

**Canada – Quebec**

- Fibrous Glass (65997-17-3): 2 fibres/cm<sup>3</sup> TWAEV (respirable) (related to Insulation wool fibers, glass wool)

**Canada – Yukon**

- Fibrous Glass (65997-17-3): 30 mppcf TWA; 10 mg/m<sup>3</sup> TWA (respirable mass) (related to Mineral wool fiber)

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM: Solid

APPEARANCE/DESCRIPTION: Asphalt roofing rolls.

COLOR: Black		ODOR: Mild petroleum odor	
TASTE: No data available		ODOR THRESHOLD: NDA	
BOILING POINT:	NDA	VAPOR PRESSURE:	NDA
MELTING POINT/FREEZING POINT:	= NDA	VAPOR DENSITY:	NDA
SPECIFIC GRAVITY:	= NDA	EVAPORATION RATE:	NDA
DENSITY:	= NDA	VOC (WT.):	NDA
BULK DENSITY:	NDA	VOC (VOL.):	NDA
WATER SOLUBILITY:	Insoluble	VOLATILES (WT.):	NDA
SOLVENT SOLUBILITY:	NDA	VOLATILES (VOL.):	NDA
VISCOSITY:	@	FLASH POINT:	NDA
HALF-LIFE:	NDA	FLASH POINT TEST TYPE:	NDA
OCTANOL/WATER PARTITION COEFFICIENT:	NDA	UEL:	NDA
COEFFICIENT OF WATER/OIL DISTRIBUTION:	NDA	LEL:	NDA
BIOACCUMULATION FACTOR:	NDA	AUTOIGNITION:	NDA
PH:	NDA		

## SECTION 10 - STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

CONDITIONS TO AVOID: Keep away from heat, ignition sources and incompatible materials.

INCOMPATIBLE MATERIALS: This product will react with strong oxidizing agents, reducing agents, strong acids and alkalis.

HAZARDOUS DECOMPOSITION PRODUCTS: Upon decomposition this product may emit hydrogen sulfide, formaldehyde, hydrogen cyanide, carbon dioxide, carbon monoxide and other low molecular weight hydrocarbons and oxides of sulfur, nitrogen, calcium and magnesium.

## SECTION 11 - TOXICOLOGICAL INFORMATION

This product has not been tested as a separate entity. Therefore, the hazards must be evaluated on the basis of the individual ingredients, and those hazards must be assumed to be additive in the absence of complete information. The hazards described in this document have been evaluated on a threshold of 1.0% for all hazardous ingredients and 0.1% for all carcinogens, mutagens, reproductive hazards and respiratory sensitizers.

ACUTE TOXICITY: Temporary irritation may be observed in the upper respiratory system, eyes, and skin. Inhalation of dusts/fumes from this product may cause a scratchy throat, congestion, and slight coughing.

CARCINOGENIC EFFECTS: When used under normal conditions, this product is not considered a carcinogen.

### COMPONENT CARCINOGENICITY:

This product contains petroleum asphalt. If heated, there is limited evidence that derivatives of asphalt fumes may cause carcinogenic effects in animals. There is inadequate evidence to support that asphalt fumes alone are carcinogenic to humans.

Asphalt Fumes (8052-42-4):

ACGIH:	A4 - Not Classifiable as a Human Carcinogen (as benzene soluble aerosol)
IARC:	Group 3 - Not Classifiable (IARC Supplement 7 [1987], Monograph 35 [1985])
NIOSH:	Potential occupational carcinogen.

This product contains crystalline silica. Crystalline silica is considered a carcinogen by IARC as well as NTP.

Crystalline Silica (14808-60-7):

NTP:	Reasonably Anticipated to be a human carcinogen (1992; <u>Sixth Annual Report on Carcinogens</u> )
IARC:	Group 2A – Limited Evidence of human carcinogenicity (IARC Monographs on Evaluation of Carcinogenic Risk of Chemicals to Humans [volume 42, 1987])
ACGIH:	A2 – Suspected human carcinogen
NIOSH:	Potential occupational carcinogen.



This product contains glass wool insulation fibers. Following a thorough review of all the medical-scientific data available at a meeting in October 2001, the IARC panel lowered the classification for glass wool insulation fibers from a Group 2B classification ("possibly carcinogenic to humans") to a Group 3 classification ("not classifiable as to carcinogenicity to humans"). IARC said that there is "no evidence of increased risks of lung cancer or of mesothelioma from occupational exposures during manufacturing of these materials, and inadequate evidence over all of any cancer risk."

Fiberglass mat, which is made from either: Continuous filament fiber glass (encapsulated) or Fibrous glass (65997-17-3):

ACGIH:	A3 - Confirmed animal carcinogen with unknown relevance to humans (related to Glass wool fibers)
NTP:	Reasonably Anticipated To Be A Carcinogen (respirable size) (related to Glass wool) (Possible Select Carcinogen)
IARC:	Monograph 81 [2002] (listed under Man-made mineral fibers), Monograph 43 [1988] (related to Insulation glass wool) (Group 3 (not classifiable))

## SECTION 12 - ECOLOGICAL INFORMATION

PRODUCT INFORMATION: This product has not been tested. Based on information related to all raw materials in the finished product it is not expected to harm ecosystems through its applied use.

ECOLOGICAL FATE: No information available for the product.

PERSISTENCE/DEGRADABILITY: No information available for the product.

## SECTION 13 - DISPOSAL CONSIDERATIONS

PRODUCT: This product, as supplied, is not regulated as a hazardous waste by the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. Comply with state and local regulations for disposal. If you are unsure of the regulations, contact your local public health department, or the local office of the EPA.

DISPOSAL: Dispose of waste material according to local, state, federal, and provincial environmental regulations.

## SECTION 14 - TRANSPORTATION INFORMATION

U.S. DOT 49 CFR 172.101:

SHIPPING NAME: Not Regulated for Transportation

TDG - CANADA - TRANSPORT OF DANGEROUS GOODS:

SHIPPING NAME: Not Classified as a Dangerous Good for Transport

## SECTION 15 - REGULATORY INFORMATION

SARA HAZARD CLASSIFICATIONS:

Acute Health: Yes Chronic Health: Yes Fire: No Pressure: No Reactive: No

US FEDERAL:

GENERAL PRODUCT INFORMATION:

Components of this product have been checked against the non-confidential TSCA inventory by CAS Registry Number. Components not identified on this non-confidential inventory are either exempt from listing (i.e. polymers, hydrates) or are listed on the confidential inventory as declared by the supplier.

**TSCA (Toxic Substances Control Act) - Section 8(a) - Inventory Update Rule - Partially Exempt Substances**

- Asphalt (8052-42-4) 60 to 50% Partially exempt chemical substance termed 'Petroleum Process Stream'
- Calcium carbonate (1317-65-3) 30 to 10% Partially exempt chemical substance under 40 CFR 710.46(b)(2)
- Silica Crystalline Quartz (14808-60-7) 0% to 20%

**CERCLA:**

This material does not contain chemicals required to be identified under CERCLA (40 CFR 302.4).

**STATE REGULATIONS:**

**COMPONENT ANALYSIS - STATE:**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS #	CA	MA	MN	NJ	PA	RI
Petroleum Asphalt (fumes)	8052-42-4	Yes	Yes	Yes	Yes	Yes	Yes
Calcium Carbonate	1317-65-3	No	Yes	Yes	No	Yes	Yes
Silica Crystalline Quartz	14808-60-7	Yes	Yes	Yes	Yes	Yes	Yes
Fiberglass mat, which is made from either: Continuous filament fiber glass (encapsulated) or Fibrous glass (*related to Mineral wool fiber)	65997-17-3	Yes	Yes	Yes	No	Yes	Yes

**CALIFORNIA SAFE DRINKING WATER AND TOXICS ENFORCEMENT ACT (PROPOSITION 65):**

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

**WARNING!**

This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

**CANADIAN WHMIS INFORMATION:**

**GENERAL PRODUCT INFORMATION:**

In Canada, these products are considered manufactured articles under the Workplace Hazardous Materials Information System (WHMIS) and are exempt.

**COMPONENT ANALYSIS - WHMIS IDL:**

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

- Silica, crystalline - quartz (14808-60-7) 50 to 10% 1 % (English Item 1406, French Item 1491)

**ADDITIONAL REGULATORY INFORMATION:**

**GENERAL PRODUCT INFORMATION:**

No information available for the product.

# COMPONENT ANALYSIS – INVENTORY:

Component	CAS #	TSCA	DSL	EINECS
Asphalt	8052-42-4	Yes	Yes	Yes
Fiberglass mat, which is made from either: Continuous filament fiber glass (encapsulated) or Fibrous glass	65997-17-3	Yes	Yes	Yes
Silica Crystalline Quartz	14808-60-7	Yes	Yes	Yes
Calcium carbonate	1317-65-3	Yes	No	Yes
Polyolefin mixture	NDA	No	No	No
SBS Polymer	NDA	No	No	No
Slag	NDA	No	No	No

## SECTION 16 - OTHER INFORMATION

PREPARATION DATE: 8/1/1994

LAST REVISION DATE: 11/2/2009

DISCLAIMER: Reasonable care has been taken in the preparation of this information, but the supplier gives no warranty of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser will make his own tests to determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental and/or consequential property damage arising out of the use of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights. Read the Material Safety Data Sheet before handling product.

For reference to the acronyms/definitions used in this MSDS please visit [www.certainteed.com](http://www.certainteed.com).

### MSDS HISTORY:

#### MSDS REVISION SUMMARY:

Date	MSDS No.	Changes
1/1/2009	CT-10124	<ul style="list-style-type: none"> <li>MSDS format change (new ANSI Z400.2004 &amp; GHS v .2007 format)</li> <li>Section 2 – GHS (v. 2007) Classifications</li> </ul>
11/2/2009	CT-10060; CT-10124	<ul style="list-style-type: none"> <li>Combined CT-10060 and CT-10124 into one MSDS</li> </ul>

*This is the end of MSDS # CT-10060 and CT-10124.*