

**MATERIAL SAFETY DATA SHEET**  
**FOR COATINGS, RESINS AND RELATED MATERIALS**

**Date Issued 09/13/10**

**SECTION I – PRODUCT INFORMATION**

MANUFACTURER'S NAME

**STELWAGON ROOFING SUPPLY, INC.**

STREET ADDRESS

**10096 SANDMEYER LANE**

CITY, STATE, AND ZIP CODE

**PHILADELPHIA, PA 19116**

EMERGENCY TELEPHONE NUMBER

**1-800-424-9300**

PRODUCT CLASS

**ASPHALT FLASHING COMPOUND**

MANUFACTURER'S CODE

IDENTIFICATION

**ST-1145**

TRADE NAME

**STELCO WET/DRY FORMULA**

**SECTION II- HAZARDOUS INGREDIENTS**

INGREDIENT	PERCENT	TLV PPM	TLV Mg/M3
PETROLEUM ASPHALT CAS # - 8052-42-4	<50%	NE	0.5 Fume
MINERAL SPIRITS CAS #- 8052-41-3	<20%	100	NE
INORGANIC FILLER CAS #- 1317-65-3	<35%	NE	10*
CELLULOSE FIBER CAS #- 9004-34-6	<10%	NE	10*
POLYMER CAS #- MIXTURE	<1%	NE	**

ADDITIONAL INFORMATION-\*AS RESPIRABLE FRACTION OF DUST. \*\* NOT ESTABLISHED

Hazardous Materials Identification System (HMIS)

Health  
1

Flammability  
2

Reactivity  
0

Personal Protection  
C

**SECTION III – PHYSICAL DATA**

BOILING RANGE: 300 °F - 390°F VAPOR DENSITY  HEAVIER THAN AIR

EVAPORATION RATE  SLOWER THAN ETHER PERCENT VOTILE BY VOLUME <30 % WEIGHT PER GALLON BY VOLUME 9.6 LBS

**SECTION IV – FIRE AND EXPLOSION HAZARD DATA**

DOT CATEGORY - N/R

FLASH POINT- 105°F Minimum

EXTINGUISHING MEDIA- CO2, FOAM, & DRY CHEMICAL

UNUSUAL FIRE AND EXPLOSION HAZARDS- CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. PRODUCTS OF COMBUSTION MAY BE TOXIC

SPECIAL FIRE FIGHTING PROCEDURES- WEAR SELF CONTAINED BREATHING APPARATUS. WATER MAY BE USED TO COOL CLOSED CONTAINERS. HIGH PRESSURE STREAM WILL SPREAD FIRE.

---

## SECTION V – REACTIVITY DATA

---

STABILITY:  STABLE

CONDITIONS TO AVOID: HEAT, FLAMES, STRONG  
OXIDIZERS

INCOMPATIBILITY (MATERIALS TO AVOID): CARBON OXIDES

HAZARDOUS DECOMPOSITION PRODUCTS: NONE

HAZARDOUS POLYMERIZATION:  WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

---

## SECTION VI-HEALTH HAZARD DATA

---

EFFECTS OF OVEREXPOSURE-**ACUTE: SKIN:** PROLONGED /REPEATED CONTACT MAY CAUSE IRRITATION, DEFATTING AND DERMATITIS.-**EYES:** MAY CAUSE SEVERE IRRITATION, REDNESS TEARING AND BLURRED VISION.-**INHALATION:** MAY CAUSE DIZZINESS, WEAKNESS, HEADACHE, UNCONSCIOUSNESS AND EVEN ASPHYXIATION.-**INGESTION** MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA.

---

EMERGENCY FIRST AID PROCEDURE-**SKIN:** REMOVE CONTAMINATED CLOTHING. WASH EXPOSED AREA. WITH SOAP AND WATER. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. **EYES:** FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. **INHALATION:** REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXIGEN. IF BREATHING STOPS, GIVE ARTIFICIAL RESPIRATION AND SEEK MEDICAL ATTENTION IMMEDIATELY. **INGESTION:** DO NOT INDUCE VOMITING. ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL. KEEP PERSON WARM AND QUIET.

---

## SECTION VII – SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ELIMINATE SOURCES OF IGNITION KEEP PRODUCT OUT OF SEWERS BY DIKING OR IMPOUNDING. SOAK UP SPILL WITH SAND OR OTHER ABSORBENT. PLACE IN CONTAINERS FOR PROPER DISPOSAL.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

---

## SECTION VIII – SPECIAL PROTECTION INFORMATION

---

RESPIRATORY PROTECTION: USE NIOSH/MSHA APPROVED RESPIRATOR WHEN TLV IS EXCEEDED.

VENTILATION: USE WITH ADEQUATE VENTILATION.

PROTECTIVE GLOVES: NITRILE RUBBER SHOULD BE USED.

EYE PROTECTION: SAFETY GOGGLES SHOULD BE USED.

OTHER PROTECTIVE EQUIPMENT: FACE SHIELD

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN COOL PLACE

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINERS TIGHTLY CLOSED.

---

## SECTION IX – REGULATORY INFORMATION

---

**CALIF. PROP. 65 • CHEMICAL WARNING** (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ).  
**WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Read and follow label directions and information given on Material Safety Data Sheets and use care when handling or using all petroleum products.

**DOT CATEGORY:** NOT REGULATED

**TSCA STATUS:** ALL CHEMICAL SUBSTANCES IN THIS PRODUCT ARE INCLUDED ON OR EXEMPTED FROM LISTING ON THE TSCA INVENTORY OF CHEMICAL SUBSTANCES.

**Disclaimer of Warranty:** The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.